

LED RECESSED VANDAL RESISTANT OUTDOOR DOWNLIGHT

4" AND 6" | RECESSED MOUNT | LED DOWNLIGHT | 1,500 LM - 2,000 LM

IP67

Benefits

- Outdoor rated IP67
- Available with Shatter Proof Polycarbonate Lenses
- Energy efficient, low glare LED Chip-On-Board light engine
- Emergency back up available
- Singular COB Light Source
- 5 year limited warranty



Application

Architectural-grade recessed LED downlight housing for medium to high ceilings combines energy efficiency with powerful lumen output. Perfect for atriums, churches, lobbies, and airports that have high ceilings.



Housing

Constructed from a round one piece high grade die-cast aluminum with a powder coat finish. Includes COB LED and reflector, (3) screw down mounting clips and a cable gland with cord. A housing safety cable is secured to faceplate. Fixture also includes an LED driver.

Mounting

Housing suitable for existing or new construction installation. Supplied with screw down mounting clips, designed to secure the fixture to an existing flat surface. Mounting Pan with hanger bars are available. Consult factory

Faceplate

Constructed from a round one piece high grade die-cast aluminum with a powder coat finish. Includes a clear tempered glass lens and silicone gasket. Faceplate is secured to the housing by three (3) tamper resistant stainless steel screws. A safety cable from the housing is secured to the faceplate for easy installation of the fixture.



Lumen Maintenance

Minimum 50,000 hours L70 life based on ANSI TM-21 calculations from LM80 standardized test results. See ordering guide for delivered lumens.

Electrical

AC 50/60Hz Electronic Direct Current Class 2 driver integrally mounted. Power Factor > 0.90. For cold weather applications (-22°C and above) use -DUN driver option.

Insulation Contact

IC rated housing rated for direct contact with loosefill blown and rolled insulation.

Dimming

(-DUN) option is a universal dimming system that works with most 3-Wire ELV, 2-Wire Incandescent and 5-Wire 0-10V fluorescent dimmers.

Listing

ETL/cETL Listed. Suitable for wet location. Assembled in USA. (IP67).

Warranty


Covered by a 5 Year Warranty to be free of defects in materials and craftsmanship. Fixture should not be installed in applications with ambient temperature above 60 degrees C. Doing so will result in reduced lamp life and voided warranty.




LED RECESSED VANDAL RESISTANT OUTDOOR DOWNLIGHT

4" AND 6" | RECESSED MOUNT | LED DOWNLIGHT | 1,500 LM - 2,000 LM


LED RECESSED VANDAL RESISTANT DOWNLIGHT ORDERING Example: DL34RB-PCUE-DUN-T50-C90


ITEM #	FINISH	LENS	DIMMING	LED	CRI
DL34R : 4-inch Recessed 	B : Black	Blank : Clear Tempered Glass	Blank : Non-Dimming (120V)	-T27 : 2700K	Blank : 80CRI
	W : White	-FR : Frosted Tempered Glass	UE-DUN : UniDim™ (120V/277V)	-T30 : 3000K	-C90 : 90CRI
	S : Silver	-PC : Clear Polycarbonate		-T35 : 3500K	
	BZ : Bronze			-T40 : 4000K	
				-T50 : 5000K	
			-T56 : 5600K		

 5 3/8" (height), 5 5/8" (width)

IP67 **1500LM**


LED RECESSED VANDAL RESISTANT DOWNLIGHT ORDERING Example: DL36RB-PCUE-DUN-T65-C90


ITEM #	FINISH	LENS	DIMMING	LED	CRI
DL36R : 6-inch Recessed 	B : Black	Blank : Clear Tempered Glass	Blank : Non-Dimming (120V)	-T27 : 2700K	Blank : 80CRI
	W : White	-FR : Frosted Tempered Glass	UE-DUN : UniDim™ (120V/277V)	-T30 : 3000K	-C90 : 90CRI
	S : Silver	-PC : Clear Polycarbonate		-T35 : 3500K	
	BZ : Bronze			-T40 : 4000K	
				-T50 : 5000K	
			-T56 : 5600K		
			-T65 : 6500K		

 8 5/8" (height), 7 7/8" (width)

IP67 **2000LM**

LED RECESSED VANDAL RESISTANT DOWNLIGHT ORDERING Example: DL36R7B-PCUE-DUN-T56

ITEM #	FINISH	LENS	DIMMING	LED	CRI
DL36R7 : 6-inch Wall Wash 	B : Black	Blank : Clear Tempered Glass	Blank : Non-Dimming (120V)	-T27 : 2700K	
	W : White	-FR : Frosted Tempered Glass	UE-DUN : UniDim™ (120V/277V)	-T30 : 3000K	
	S : Silver	-PC : Clear Polycarbonate		-T35 : 3500K	
	BZ : Bronze			-T40 : 4000K	
				-T50 : 5000K	
			-T56 : 5600K		
			-T65 : 6500K		

 8 5/8" (height), 7 7/8" (width)

IP67 **2000LM**